



ITEM	NAME OF PART	MATERIAL	NOTES
6	Screw 2	Steel	M2.5/Zn Plated
5	Screw 1	Steel	M2/Zn Plated
4	Cage	Copper Alloy	M2/Ni Plated
3	Clamp	Copper Alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电压 /Rated Voltage(V)/Current(A)	300/8	/	300/8
EC 标准 /IEC Standard:			
过压类别 /Overvoltage Category /污染等级 /Pollution Degree	II/2		
额定电压/电流 /Rated Voltage(V)/Current(A)	250/7		
额定脉冲电压 (KV) /Rate Impulse Voltage(KV)	2.5		
扭矩/扭距 /Torque Tightening(N·m/Lb.in)	M2: 0.2/1.77		
线径范围 (硬线和软线) /Wire Range(rigid and flexible)(mm ² /AWG)	0.5~1.5/28~16		
剥线长度 /Stripping length(mm)	3.81/N=02~24P		
使用温度范围 /Operating temperature(°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		

SURFACE:

宁波三安电子科技有限公司
Sanan Electrical Technology Co. Ltd

NAME: 15ESAKM-3.81-XXP-1Y-00A(H)

DRAWING NO.: SCALE: SHEET 1/1

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	mm (inch)
TYPE:	

公差 (General Tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
±Z	±0.1/10	±0.15	±0.2	±0.25	±0.3	±0.35	±0.4	±0.5	±0.6	±0.7	±0.8	±1.0	±1.2	±1.5

D