



2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C D
额定电压/电流	Rated Voltage(V)/Current(A)	300/8	300/8
额定冲击电压	Rated Voltage(V)/Current(A)	/	/
EC 标准	IEC Standard:		
过压类别	Overvoltage Category/污染等级	II/2	
额定电压/电流	Rated Voltage(V)/Current(A)	250/7	
额定冲击电压	Rate Impulse Voltage(KV)	2.5	
间距/Pitch	mm/线数范围/Polis	3.81/N=02~24P	
使用温度范围	Operating temperature(°C)	-40~+105	
符合RoHS环保要求	Conform to RoHS	Yes	

SURFACE:

MATERIAL: 宁波三安电子科技有限公司  
Sanan Electrical Technology Co. Ltd

NAME: 15ESAWC-3.81-XXP-1Y-00A(H)

MAT NO.:	STATUS:	APPD:	CHKD:	DRT:	SIZE: A4	TYPE: A4	SCALE:	REV	SHEET
					mm (inch)				1/1

公差 (General tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

公差	±0.1/10
公差	±Z