



7	Cover 2	PA66	UL94V-0
6	Spring	Stainless steel	
5	Clamp	Copper alloy	Sn plated
4	Middle housing 2	PA66	UL94V-0
3	Middle housing 1	PA66	UL94V-0
2	Side housing	PA66	UL94V-0
1	Cover 1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/151	150/151	300/10
IEC 标准 / IEC Standard:	III/3	III/2	II/2
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电流 / Rated Voltage(V)/Current(A)	320/20	/	/
额定脉冲电压 / Rated Impulse Voltage(KV)	4	/	/
线径范围 (硬线和软线) / Wire Range(rigid and flexible)(mm <sup>2</sup> / AWG)	0.2~2.5 / 22~14		
间距 / Pitch(mm) / 线数范围 / Poles	5.00 / N=02~24P		
剥线长度 / Stripping length(mm)	9~10		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求 / Conform to RoHS	Yes		
标准颜色编号 / Standard color number:	428C		

MATERIAL: SURFACE: PANTONE:

MAT NO.:  
STATUS:  
APPD:  
CHKD:  
DRFT:

NAME: **宁波三安电子科技有限公司**  
Sanan Electrical Technology Co. Ltd

DRAWING NO.: **BESAKG-5.0-XXP-11-1001A(H)**  
TYPE: SCALE: SHEET 1/1

公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)					
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10							
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z							
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z							

1 2 3 4 5 6

D B A