



↑ A

5	Spring	Stainless steel	
4	Clamp	Copper alloy	Sn Plated
3	Button	PA66	UL94V-0
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard: B C D			
额定电压/电流/Rated Voltage(V)/Current(A)		300/10	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2
额定电压/电流/Rated Voltage(V)/Current(A)			320/20
额定脉冲电压(KV)/Rate Impulse Voltage(KV)			4
额定范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)			0.2~2.5/26~12
间距/Pitch(mm)/线数范围/Poles			5.0/N=02~24P
剥线长度/Stripping length(mm)			9-10
使用温度范围/Operating temperature(°C)			-40~+105
符合RoHS环保要求/Conform to RoHS			Yes
SURFACE: /			

MATERIAL:
MAT NO.:
STATUS:
APPD:
CHKD:
DRFT:

NAME:
宁波三安电子科技有限公司
Sanan Electrical Technology Co. Ltd

DRAWING NO.:
2ESAKD-5.0-XXP-1Y-00A(H)

SIZE: A4
SCALE: REV 1/1

公差表/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~	~	~	~	~	~	~	~	~	~	~	~	~	~
3	6	10	18	30	50	80	120	180	250	315	400	500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10
±Z