



5	Spring	Stainless Steel		
4	Pin	Copper	Sn Plated	
3	Housing-2	PA66	UL94V-0	
2	Housing-1	PA66	UL94V-0	
1	Cover	PA66	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	
UL 标准/UL Standard:		B	C	D
额定电压/电压/Rated Voltage(V)	Current(A)	300/10	/	/
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/符采等级/ Pollution Degree	III/3	III/2	II/2	
额定电压/电压/Rated Voltage(V)	Current(A)	130/10	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		2.5	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)		0.2~1.5/28~14		
间距/Pitch(mm)/线数范围/Poles		3.5/N=02~24P		
剥线长度/Stripping length(mm)		10		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		
标准颜色编号/Standard color number:		PANTONE 7534U		

MATERIAL:

MAT NO.:

STATUS:

APPD:

CHKD:

DRFT:

SURFACE:

宁波三安电子科技有限公司  
Sanan Electrical Technology Co. Ltd

NAME:

RESAKR-3.5-XXP-11-01A(H)

DRAWING NO.:

TYPE:

SIZE: A4

MM  
INCH

SCALE:

REV SHEET 1/1

公差/General tolerances(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10

±Z