



5	Screws	Steel	M3/Zn Plated
4	cage	Copper alloy	Ni Plated
3	Pin	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C D
额定电压/电流	/Rated Voltage(V)/Current(A)	300/15	300/10
EC 标准	/EC Standard:		
过压类别	/Overvoltage Category/污染等级	III/3	II/2 II/2
污染度	/Pollution Degree		
额定电压/电流	/Rated Voltage(V)/Current(A)	/	320/20
额定脉冲电压	(KV)/Rate Impulse Voltage(KV)		4
额定扭矩	(N·m/Lb.in)	M3, 0.8/7.02	
线径范围	(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	2.5/28~12	
导线长度	/Striping length(mm)	5.0/N=02~22P	
使用温度范围	/Operating temperature(°C)	-40~+105	
符合RoHS环保要求	/Conform to RoHS	Yes	

SURFACE:

MATERIAL:

MAT NO.:

STATUS:

APPD:

CHKD:

DRT:



® 宁波三安电子科技有限公司
Sanan Electrical Technology Co., Ltd

NAME: ZESAKR-5.0-XXP-1Y-00A(H)

DRAWING NO.:

SIZE: A4

mm
(inch)

TYPE:

SCALE:

SHEET 1/1

公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	

0.1/10
±Z