



6	Screw	Steel	Zn Plated
5	Spring	Stainless steel	
4	Clamp	Copper Alloy	
3	Button	PA66	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/10	/	300/10
IEC 标准 / IEC Standard:	III/2		
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/2		
额定电压/电流 / Rated Voltage(V)/Current(A)	320/20		
额定脉冲电压 / Rated Impulse Voltage(KV)	4.0		
额定扭矩 / Torque Tightening(N·m/Lb·in)	M2.5 0.4/3.54		
导线范围 / 硬线和软线 / Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/26~12		
间距 / Pitch(mm) / 线数范围 / Poles	5.0/N=N=02~24P		
剥线长度 / Stripping length(mm)	9~10		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求 / Conform to RoHS	Yes		

SURFACE:


宁波三安电子科技有限公司
 Sanan Electrical Technology Co. Ltd

NAME: **ZESAKDAM-5.0-XXP-1Y-00A(H)**
 DRAWING NO.:

MATERIAL:	
MAT NO.:	
STATUS:	
APPD.:	
CHKD.:	
DRAFT:	
SIZE: A4	mm (inch)
TYPE:	SCALE: REV SHEET

公差 (General tolerances)(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±

1 2 3 4 5 6