



III 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/10	50/10	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category /污染等级/ Pollution Degree	III/3	II/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	160/13.4	160/13.4	320/13.4
额定电涌电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~1.5/28~16		
间距/Pitch(mm)/线数范围/Poles	3.50	N=04~48P	
绝缘长度/Stripping length(mm)	10~11		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:  
STATUS:  
APPD:  
CHKD:  
DRTT:

NAME: 1ESAKNHBG-3.5-XXP-1Y-100A(H)  
DRAWING NO.:

SIZE: A4  
SCALE: SHEET 1/1

公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

**宁波三安电子科技有限公司**  
 Sanan Electrical Technology Co. Ltd